

KALKULIN FLYDENDE®

Cleaner for floors, walls, fixtures and fittings. Particularly useful in the food industry, but also good for washing equipment in the transport sector. Dissolves fat, oil, protein and ordinary dirt. Prevents limescale during the work process.



ADVANTAGES:

- the Nordic Swan label, which ensures that it is among the most effective and least environmentally harmful within the product category
- prevents limescale to avoid lime deposits on surfaces
- oil and fat remover with low pH value

DOSAGE:

Manuel cleaning: 1-2 %

Low pressure: 1-5 % *

Fomigation: 1-5 % *

*)depending on the degree of contamination

pH-value in solution: approx. 8-9

pH-value in 100 %: appr. 11,2

NOTE!

Undiluted KALKULIN can attack aluminium and paint.

USER INSTRUCTIONS:

Manual cleaning. Apply with brush, sponge or broom. Reaction time 1-10 min. Flush with water. Very dirty surfaces can be machined manually.

When cleaning protein-containing debris in large kitchens and butcher's departments, application through foam equipment at max. 30 degrees C improve cleaning result.

Materials and tools which will come into contact with food are to be thoroughly flushed with clean water.

When washing equipment in the transport sector, use hot water for best result (60-95 gr.C) .Soak for 1-10 minutes. Rinse with cold water.

PACKAGING:

200 ltr. plastic drum (2 pcs./pallet)

25 ltr. plastic container (12 pcs./pallet)

10 ltr. plastic container (24 pcs./pallet)

5 ltr. plastic container (3 pcs. pr. colli. 108/pallet)

ACCREDITATION:



SAFETY:



ITEM NO.:

05-04-2022/gk

REVISION:

1005xxxx

CIRCULAR ECONOMY



The packaging can be recycled. Rinse the can with clean water and use the rinsing water for cleaning. Cross out any danger labels before sending the container to recycling.